



Friedrich-Alexander-Universität
Technische Fakultät

Chair for Computer Science 6 (Data Management)

Deep Transfer Learning Model Selection


In A Time Series Modeling Context

Melanie Bianca Sigl

`melanie.sigl@fau.de`


July 5, 2022

Deep Transfer Learning as State-of-the-Art




Deep Transfer Learning as State-of-the-Art

- **Reduce time to select a hyperparameter space**
- **Reduces training time**
- Reduces amount of models to train
- **Avoids overfitting**
- Even obtain **better results**




Three Signs Transfer Learning was Successful¹




¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.

Three Signs Transfer Learning was Successful¹




¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.

Three Signs Transfer Learning was Successful¹




¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.

Three Signs Transfer Learning was Successful¹




¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.

Three Signs Transfer Learning was Successful¹



¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.


Three Signs Transfer Learning was Successful¹



¹adapted and extended from: Torrey, L., & Shavlik, J., *Transfer Learning*, Handbook of Research on Machine Learning Applications and Trends, 2010.


Possible Modifications of a Source DL Model: Which to Perform?

1. Base: Pre-trained DL Model




Possible Modifications of a Source DL Model: Which to Perform?

1. Base: Pre-trained DL Model
2. Change number of output neurons




Possible Modifications of a Source DL Model: Which to Perform?

1. Base: Pre-trained DL Model
2. Change number of output neurons
3. Freeze first n hidden layers, fine-tune others or re-initialize weights



Possible Modifications of a Source DL Model: Which to Perform?

1. Base: Pre-trained DL Model
2. Change number of output neurons
3. Freeze first n hidden layers, fine-tune others or re-initialize weights
4. Add new hidden layer



Features of a DL-Model are Transferable

Transferability is negatively affected by:

- Specialization of higher layer neurons → specialization towards target task²
- Increasing dataset and/or task dissimilarity³

Transfer learning is powerful:

- Initializing a network with transferred features results in a generalization boost that lingers after fine-tuning
- When target training dataset is significantly small
- Training of a large DL model without overfitting

²Jason Yosinski et al. "How transferable are features in deep neural networks?" In: *Advances in Neural Information Processing Systems* 27. Ed. by Z. Ghahramani et al. Curran Associates, Inc., 2014, pp. 3320–3328.

³Karl R. Weiss, Taghi M. Khoshgoftaar, and Dingding Wang. "A survey of transfer learning". In: *J. Big Data* 3 (2016), p. 9
Hassan Ismail Fawaz et al. "Transfer learning for time series classification". In: *IEEE International Conference on Big Data, Big Data 2018, Seattle, WA, USA, December 10-13, 2018*. Ed. by Naoki Abe et al. IEEE, 2018, pp. 1367–1376

Abundance of Available DL Models: Which DL Model to Choose?

Numerous "model repositories" exist, such as:



Problem:


An abundance of (freely) available pre-trained DL models complicates selection of an *appropriate* DL model for successful Transfer Learning.

Design and build a **repository** to support the **search and selection** of one deep learning model for **transfer learning** such that, for a given new dataset and its task, the obtained model receives a **better performance measure** than training such a model from scratch.


Leading Hypothesis

If the training data of a stored model is similar to those of the new dataset, then this stored model is suitable for Transfer Learning.


Transfer Learning Framework




Transfer Learning Framework




Transfer Learning Framework




Transfer Learning Framework




Transfer Learning Framework



Transfer Learning Framework



Transfer Learning Framework



Transfer Learning Rarely Used in a Time Series Modeling Context

Transfer Learning for *Univariate* Time Series



- Ye and Dai [YD18]: Time series forecasting. Extract characteristics from univariate time series with extreme learning machine with kernels, train multiple models on these information, create ensemble models.⁴
- He, Pang, and Si [HPS19]: (Financial) time series forecasting. Train DL model on two source datasets.⁵
- Ye and Dai [YD21]: Time series forecasting. Find similar time series with DTW and Jensen-Shannon divergence, train CNN on similar time series and then fine-tune on both query and similar time series.⁶

⁴Rui Ye and Qun Dai. “A novel transfer learning framework for time series forecasting”. In: *Knowl. Based Syst.* 156 (2018), pp. 74–99.

⁵Qi-Qiao He, Patrick Cheong-lao Pang, and Yain-Whar Si. “Transfer Learning for Financial Time Series Forecasting”. In: *PRICAI 2019: Trends in Artificial Intelligence - 16th Pacific Rim International Conference on Artificial Intelligence, Cuvu, Yanuca Island, Fiji, August 26-30, 2019, Proceedings, Part II*. ed. by Abhaya C. Nayak and Alok Sharma. Vol. 11671. Lecture Notes in Computer Science. Springer, 2019, pp. 24–36.

⁶Rui Ye and Qun Dai. “Implementing transfer learning across different datasets for time series forecasting”. In: *Pattern Recognit.* 109 (2021), p. 107617.

Fawaz et al.: Transfer Learning for Time Series Classification⁷



- 85 univariate time series + CNN
- Brute force Transfer Learning
- Replace output layer with new softmax layer and fine-tune
- 71/85 better with similarity
- Nearest neighbor not always best, sometimes 2nd nearest neighbor

⁷Hassan Ismail Fawaz et al. "Transfer learning for time series classification". In: *IEEE International Conference on Big Data, Big Data 2018, Seattle, WA, USA, December 10-13, 2018*. Ed. by Naoki Abe et al. IEEE, 2018, pp. 1367–1376.

Searching Datasets for Transfer Learning




- Natural Language Processing (NLP) such as sentiment analysis, part-of-speech tagging, and named entity recognition. [RP17; Akd20; SLE18; LM20; Lin+19; Bä18]
 - [Lin+19]: Extract textual features such as type-token ratio, word overlap, phonological distance; train ensemble of decision-trees; select high-resource language for transfer learning for a low-resource language.
- Image datasets: [Bha+20; Sch+18; BEF19; Pra+19]
 - Compute dataset difficulty of dataset to search for datasets with similar difficulty [Sch+18; Ist+19]
 - [Pra+19]: Propose *dataset similarity ranker* for image datasets. Extract image related features, train several classifiers to predict which feature vector belongs to which dataset, ensemble predictions.
- Extracted features depend on type of dataset (text vs. image). Various similarity functions used.

Data Set Characteristics for Similarity


Dataset Used: NASA's Lithium Ion Battery Dataset

- NASA's Li-Ion battery dataset consisting of 34 data sets [SG07]
- In [Goe+08] the authors detail how they obtained the measurements of these batteries
- Battery EOL after losing 30% of its capacity.
- Datasets can be used for Predictive Maintenance and Remaining Useful Life (RUL) prediction.
- *State-of-Health* (SOH) is commonly used for RUL prediction. It states the current condition of a battery compared to its initial capacity. $\frac{\text{current capacity}}{\text{initial capacity}} \%$

Dataset Used: NASA's Lithium Ion Battery Dataset




Lithium Ion Batteries State-of-Health of Each Battery



Naive Approach to Compute Time Series Similarity

- Descriptive statistics: minimum, maximum, mean, median, variance, standard deviation, quantiles (0.05, 0.25, 0.75, 0.95)
- Use Euclidean distance to order dataset.
- Perform brute force transfer learning where for each dataset the DL model of the first nearest neighbour is reused.
- Reuse: Re-initialize last layer (output layer) and retrain whole network.


Transfer Results Using Naive Dataset Similarity









Currently Implemented Naive Time Series Similarity: Results

Summary


- Transfer learning shows positive improvement in some cases.
- Other cases show negative transferability.
- First nearest neighbour usually performs poorly.
- Second nearest neighbour also performs poorly.
- Distributional statistics not sufficient.





Create Reference Time Series Using DTW with Barycenter Averaging



Transfer Results: Naive Approach vs. DTW Barycenter Averaging



Transfer Results: Naive Approach vs. DTW Barycenter Averaging



Summary

- DTW Barycenter Averaging generally performs better (first five neighbours)
- Interesting: Farthest neighbours of naive approach performs better
- Some datasets notoriously successful, whereas some always yield negative transfer results

Ways Forward to Improve Naive Similarity

- Extract **time-series specific characteristics** such as trend, seasonality, chaos, skewness, and kurtosis. Thus, extracting similar characteristics as Wang, Smith, and Hyndman [WSH06]⁸.
- **Extract further characteristics** as Fulcher and Jones [FJ14], albeit maybe not as much as they did (they extracted over 9,000 features).⁹

⁸Xiaozhe Wang, Kate Smith, and Rob Hyndman. "Characteristic-Based Clustering for Time Series Data". In: *Data Mining and Knowledge Discovery* 13.3 (May 2006), pp. 335–364.


⁹Ben D Fulcher and Nick S Jones. "Highly comparative feature-based time-series classification". In: *IEEE Transactions on Knowledge and Data Engineering* 26.12 (2014), pp. 3026–3037.

Ways Forward to Improve DTW Barycenter Averaging Similarity



- Currently: Sum DTW distances of each dataset attribute.
- Find similar dataset similarity based on **individual attribute similarities**.
- DTW Barycenter Averaging method yields a reference time series that may not reflect the variability of a set of time series. Extend it with a **confidence interval**.

Data Structures for Transfer Learning

User Story and Architecture



User Story and Architecture



Summary and Ways Forward

Summary and Ways Forward

- Improve naive similarity approach by using dedicated time series characteristics
- Improve DTW Barycenter Averaging approach by extending to search for a similar attribute among all available attributes of another dataset; extend it by introducing a confidence interval.
- Use datasets from another domain such as NASA's turbofan engine degradation dataset
- Extend current regression task to time series classification



Friedrich-Alexander-Universität
Technische Fakultät

Chair for Computer Science 6 (Data Management)

Deep Transfer Learning Model Selection

In A Time Series Modeling Context

Melanie Bianca Sigl

`melanie.sigl@fau.de`

July 5, 2022

Appendix

Bibliography i

- [Akd20] Arda Akdemir. “Research on Task Discovery for Transfer Learning in Deep Neural Networks”. In: *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: Student Research Workshop, ACL 2020, Online, July 5-10, 2020*. Ed. by Shruti Rijhwani et al. Association for Computational Linguistics, 2020, pp. 33–41.
- [BEF19] Kevin Bascol, Rémi Emonet, and Elisa Fromont. “Improving Domain Adaptation By Source Selection”. In: *ICIP 2019 - IEEE International Conference on Image Processing*. Taïpei, Taiwan: IEEE, Sept. 2019.
- [Bha+20] Bishwaranjan Bhattacharjee et al. “P2L: Predicting Transfer Learning for Images and Semantic Relations”. In: *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR Workshops 2020, Seattle, WA, USA, June 14-19, 2020*. IEEE, 2020, pp. 3284–3293.
- [Bä18] Jesper Bäck. “Domain similarity metrics for predicting transfer learning performance”. PhD thesis. Linköping University, 2018.
- [Faw+18] Hassan Ismail Fawaz et al. “Transfer learning for time series classification”. In: *IEEE International Conference on Big Data, Big Data 2018, Seattle, WA, USA, December 10-13, 2018*. Ed. by Naoki Abe et al. IEEE, 2018, pp. 1367–1376.

Bibliography ii

- [FJ14] Ben D Fulcher and Nick S Jones. “Highly comparative feature-based time-series classification”. In: *IEEE Transactions on Knowledge and Data Engineering* 26.12 (2014), pp. 3026–3037.
- [Goe+08] Kai Goebel et al. “Prognostics in Battery Health Management”. In: *IEEE Instrumentation Measurement Magazine* 11.4 (2008), pp. 33–40.
- [HPS19] Qi-Qiao He, Patrick Cheong-lao Pang, and Yain-Whar Si. “Transfer Learning for Financial Time Series Forecasting”. In: *PRICAI 2019: Trends in Artificial Intelligence - 16th Pacific Rim International Conference on Artificial Intelligence, Cuvu, Yanuca Island, Fiji, August 26-30, 2019, Proceedings, Part II*. Ed. by Abhaya C. Nayak and Alok Sharma. Vol. 11671. Lecture Notes in Computer Science. Springer, 2019, pp. 24–36.
- [Ist+19] Roxana Istrate et al. “TAPAS: Train-Less Accuracy Predictor for Architecture Search”. In: *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*. AAAI Press, 2019, pp. 3927–3934.

Bibliography iii

- [Lin+19] Yu-Hsiang Lin et al. “Choosing Transfer Languages for Cross-Lingual Learning”. In: *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28-August 2, 2019, Volume 1: Long Papers*. Ed. by Anna Korhonen, David R. Traum, and Lluís Màrquez. Association for Computational Linguistics, 2019, pp. 3125–3135.
- [LM20] Samuel Louvan and Bernardo Magnini. “How Far Can We Go with Data Selection? A Case Study on Semantic Sequence Tagging Tasks”. In: *Proceedings of the First Workshop on Insights from Negative Results in NLP, Insights 2020, Online, November 19, 2020*. Ed. by Anna Rogers, João Sedoc, and Anna Rumshisky. Association for Computational Linguistics, 2020, pp. 15–21.
- [Pra+19] Ameya Prabhu et al. ““You might also like this model”: Data Driven Approach for Recommending Deep Learning Models for Unknown Image Datasets”. In: *CoRR abs/1911.11433 (2019)*. arXiv: **1911.11433**.
- [RP17] Sebastian Ruder and Barbara Plank. “Learning to select data for transfer learning with Bayesian Optimization”. In: *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP 2017, Copenhagen, Denmark, September 9-11, 2017*. Ed. by Martha Palmer, Rebecca Hwa, and Sebastian Riedel. Association for Computational Linguistics, 2017, pp. 372–382.

Bibliography iv

- [SG07] Bhaskar Saha and Kai Goebel. *Battery Data Set*. NASA Ames Prognostics Data Repository. NASA Ames Research Center, Moffett Field, CA. 2007. URL: <http://ti.arc.nasa.gov/project/prognostic-data-repository> (visited on 05/09/2022).
- [Sch+18] Florian Scheidegger et al. “Efficient Image Dataset Classification Difficulty Estimation for Predicting Deep-Learning Accuracy”. In: *CoRR* abs/1803.09588 (2018). arXiv: **1803.09588**.
- [SLE18] Lex Razoux Schultz, Marco Loog, and Peyman Mohajerin Esfahani. “Distance Based Source Domain Selection for Sentiment Classification”. In: *CoRR* abs/1808.09271 (2018). arXiv: **1808.09271**.
- [WSH06] Xiaozhe Wang, Kate Smith, and Rob Hyndman. “Characteristic-Based Clustering for Time Series Data”. In: *Data Mining and Knowledge Discovery* 13.3 (May 2006), pp. 335–364.
- [WKW16] Karl R. Weiss, Taghi M. Khoshgoftaar, and Dingding Wang. “A survey of transfer learning”. In: *J. Big Data* 3 (2016), p. 9.
- [YD18] Rui Ye and Qun Dai. “A novel transfer learning framework for time series forecasting”. In: *Knowl. Based Syst.* 156 (2018), pp. 74–99.

Bibliography v

- [YD21] Rui Ye and Qun Dai. “Implementing transfer learning across different datasets for time series forecasting”. In: *Pattern Recognit.* 109 (2021), p. 107617.
- [Yos+14] Jason Yosinski et al. “How transferable are features in deep neural networks?” In: *Advances in Neural Information Processing Systems 27*. Ed. by Z. Ghahramani et al. Curran Associates, Inc., 2014, pp. 3320–3328.